

Exide Equipment Gel

Marine and Multifit



EXIDE[®]
BATTERIES

Exide Equipment Gel

Marine and Multifit

- › Absolutely maintenance free
- › Suitable for long resting periods
- › No location constraints (safe for cabin mount)
- › Safe and clean (spark & spill-proof)
- › Internal gas recombination
- › Suitable for side mount, till 90°
- › Up to 30% space for batteries saved
- › High vibration & tilt resistant

Battery	Volt	Capacity	Cold cranking amper	Length mm	Width mm	Height mm	Position of terminal	Terminal	Hold down	Quantity
GEL12-14	12	14 AH (c20)	150 A (EN)	150	90	145	1	B		
GEL12-16	12	16 AH (c20)	100 A (EN)	180	75	165	0	G		
GEL12-19	12	19 AH (c20)	170 A (EN)	185	80	170	0	G		
GEL12-30	12	30 AH (c20)	180 A (EN)	197	132	186	1	G-M6		
ES1000-6	6	190 AH (c20)	900 A (EN)	244	190	275	0	1	B0	
ES1100-6	6	200 AH (c20)	950 A (EN)	244	190	275	0	1	B0	
ES290	12	25 AH (c20)	240 A (EN)	166	175	125	0	G-M5	B0	
ES450	12	40 AH (c20)	280 A (EN)	210	175	175	0	19	B4	
ES650	12	56 AH (c20)	460 A (EN)	278	175	190	0	1	B13	
ES900	12	80 AH (c20)	540 A (EN)	353	175	190	0	1	B13	
ES950	12	85 AH (c20)	460 A (EN)	330	171	236	1	1	B0	
ES1200	12	110 AH (c20)	760 A (EN)	284	267	226	2	1	B0	
ES1300	12	120 AH (c20)	750 A (EN)	349	175	290	0	1	B0	
ES1350	12	120 AH (c20)	760 A (EN)	513	189	223	3	1	B0	
ES1600	12	140 AH (c20)	900 A (EN)	513	223	223	3	1	B0	
ES2400	12	210 AH (c20)	1030 A (EN)	518	274	238	3	1	B0	