

4 Load

Chargers
www.4load.de



4 Load

Chargers
www.4load.de



4Load chargers are primarily connected chargers with pulse maintenance. They ensure a maximum battery lifespan and are suitable for all types of lead batteries. Thanks to the IU charg-

ing characteristic and an impulse charge, these devices are equally suitable for maintaining battery charge. All devices are splashproof and correspond to the protective system IP 65.

Item No.	Voltage	Ampere	Scope	Length mm	Width mm	Height mm	Quantity
CB-0.8	12 V	0,8 A	1 AH - 30 AH	140	60	50	
CB-3.6	12 V	3,6 A	1 AH - 120 AH	182	60	42	
CB-7.0	12 / 24 V	3,5 A / 7 A	10 AH - 230 AH	200	80	50	

Item No.	Description	Quantity
CB-START1	Display stand + desk display + 2 x Charge Box 0.8, + 5 x Charge Box 3.6 + 2 x Charge Box 7.0	
CB-START2	Display stand + desk display + 5 x Charge Box 3.6 + 4 x Charge Box 7.0	
CB-POSGROSS	Without charger! Place for 8 charger, no metter witch combination	
CB-POSKLEIN	Without charger! Place for 1 show apparat (open case) or 4 chargers	
E-001	Replacement cables for all three charger versions	
E-002	Replacement cables for all three charger versions	
E-003	Replacement cables for all three charger versions	
E-004	Adapter cable BMW-plug for cigarette lighter	

Product line:	12 V / 24 V 4-Load chargers
Model:	Fully automatic charger, microprocessor for accurate charging control, accurate and correct charging voltage
Protective system:	Charge box 0.8: IP 60 (dust-tight) Charge box 3.6 + 7.0: IP 65 (dust-tight + splash-proof); for indoor use
Safety:	reverse battery protection, overheat protection, non-sparking
Battery types:	Lead/acid batteries, gel batteries, AGM batteries, SLA batteries
Charging characteristic:	IUOU charging characteristic
Accessories:	Bag + various connecting cables (battery tongs, cigarette lighter, clamping ears)

Properties:	General: LED charging status display
	Charge box 0.8: adaptive charger, maintenance charge + permanent charge
	Charge box 3.6: 0.8 A or 3.6 A charging characteristic can be selected pulse charge + maintenance charge + permanent charge
	Charge box 7.0: automatic 12 V or 24 V recognition Pulse charge + maintenance charge + permanent charge – more precise charging status recognition (25 % / 50 % / 75 % / 100 %), 16 V boost function, can be used as 12 V voltage aggregate
Use:	Scooters – motorcycles – passenger cars – trucks – agricultural machinery – tractors – buses – construction equipment – rehab vehicles – boats