# Safe handling of lithium batteries

Guide for creating product-specific Battery Information Sheets

Page 1 from 6

Source: ZVEI I information leaflet No. 2e – Edition May2016

## **Preliminary note:**

This guide is not aimed at users of batteries. In each case, the manufacturer's recommendations (in product-specific data sheets, operating instructions/manuals or product data sheets), have priority over this guide.

The term lithium batteries encompasses a broad field of products with various designs and chemical compositions. Therefore, this guide can highlight only general information and procedures for creating product-specific data sheets.

When commissioning, storing, working with and on batteries as well as decommissioning and disposing of them, the instructions contained herein are to be adhered to strictly and without exception. In cases of doubt, please be sure to contact the manufacturer for clarification.

Due to their product properties and performance data, lithium batteries serve various applications. These include not only portable and stationary applications, but also applications in the automotive industry and industrial applications.

The term "lithium batteries" refers to non-rechargeable and rechargeable systems. This guide refers to both systems. The instructions listed in the data sheet refer to lithium batteries as well as lithium cells, even if most instructions speak only of lithium batteries for the sake of easier readability.

With the REACH Regulation 1907/2006/EC, the European chemicals legislation has been harmonized, thereby redefining various duties. REACH requires, for example, that the supplier of a substance/mixture provides a safety data sheet (SDS) to the customer. In connection with batteries under European law any dissemination of REACH -SDS is not necessary because batteries by definition are products, where SDS are not necessary.

## 1. Identification of the substance/preparation and of the company/undertaking

## intAct Bike-Power Lithium

Lithium-iron-phosphate-battery (LiFePO4)

Stefan Keckeisen Akkumulatoren e.K. Europastraße 9 • D-87700 Memmingen Phone: +49 (0)8331/94444-0 Fax: +49 (0)8331/94444-9 www.intact-batterien.de

## 2. Hazards identification

When handled properly and in accordance with the parameters specified by the manufacturer, lithium batteries are safe during use. Improper handling or conditions leading to improper operation can cause leakage of battery substances and products of decomposition and reactions associated with these, which can cause personal injury and environmental damage.

Since a wide variety of chemical substances are used, always follow the manufacturer's directions for immediate measures and first-aid measures in the event of an accident.

Lithium batteries have a gas-tight seal and are safe insofaras they are used and handled in accordance with the manufacturer's specifications.

#### Warning !

Do not charge batteries if they are not rechargeable battery systems.

When recharging batteries, never use chargers which are unsuitable for the battery type.

Do not short-circuit them. Do not inflict mechanical damage (puncturing, deforming, disassembling etc.). Do not heat them above the permitted temperature or burn them. Keep batteries away from small children. Always store batteries in a dry and cool place.

In general, contact with leaking battery substances can pose a danger to personalhealth and the environment. For this reason, when coming into contact with batteries with a conspicuous appearance (leaking substances, deformed, discoloured, dented or the like), sufficient body and breathing protection is required. Lithium batteries can, for example, react very strongin combination with fire. This can result in battery components being ejected with considerable force.



## Handling and operational safety:

Lithium batteries are always to be handled in accordance with the manufacturer's specifications. This is true particularly for complying with the limits for maximum current load, charging and end-point voltages, and mechanical and thermal loads.

Usually product packages are marketed that have already been matched. Such products are in no wise to be modified or tampered with, since that could result in substantial safety hazards.

Use the charging process tailored to the respective cell type of a rechargeable battery.

#### Danger !

As with other batteries, so also for lithium batteries it is true that even when thought to be discharged, they can still represent a source of danger. On the one hand, they can deliver a very high short-circuit current. On the other hand, even in the state of the minimum permitted end-point voltage, lithium batteries with a high voltage (over 75 Volts) can pose a danger of a lethal electric shock.

For most products, too deep a discharge leads to permanent damage. Deep-discharged lithium batteries are no longer permitted to be charged or operated.

In all cases, avoid excessive charging voltages and overcharging. They can lead directly to critical situations, but also have a negative impact on battery life. For this reason, some manufacturersrecommend gentle charging processes, which reduce the currently available energy, but by means of the lower charging voltage lead to a significantly lengthened product life.

If additional instructions are needed at this point, they can be taken, for example, from DIN EN 62133 "Secondary cells and batteries containing alkaline or other non-acid electrolytes –Safety requirements for portable sealed secondary cells, and for batteries made from them, for use in portable applications" as well as DIN EN 60086-4"Primary batteries, Part 4: Safety of lithium batteries".

## 3. Composition/Information on ingredients

The respective substances are to be taken from the manufacturer and product-specific data sheets for lithium batteries.

Note: Lithium batteries are products which release no substances when used properly.

## 4. First aid measures

When handled and stored properly, lithium cells and batteries do not represent a source of danger.

Since, depending on the manufacturer, various ingredients are used, in the case of damage always follow the instructions in the respective manufacturer's product-specific data sheets.

## Skin or eye contact:

If the substances come into contact with the skin or eyes thoroughly rinse the affected areas with water for at least 15 minutes. In the event of eye contact, in addition to thoroughly rinsing with water, always contact a doctor.

## Burns:

If burns are caused, treat them accordingly. Likewise, we urgently recommend contacting a doctor.

#### **Respiratory tract:**

Leave the room immediately if there is an intensive smoke build-up or release of gas. Call in a doctor if there are large quantities and irritation of the airways. If possible provide for sufficient ventilation

#### Swallowing:

Rinse out the mouth and around the mouth with water. Immediately call for the help of a doctor.

## 5. Fire-fighting measures

Fires from lithium batteries in use (such as in a laptop or electric vehicle) can in principle be fought with water. Differentiating between various systems of lithium batteries at the time of a fireis generally not possible and is unnecessary.

Due to the design and the battery properties, no additional or special extinguishing agents need to be available, since the batteries are protected accordingly. Fire surrounding the batteries is to be fought with conventional extinguishing agents. The fire of a battery cannot be considered separately from the surrounding fire.



The cooling effect of water effectively impedes fire from spreading to battery cells which still have not reached the critical ignition temperature ("thermal runaway").

Use of water is also favourable in light of its wide availability.

Hybrid or fully electric vehicles pose no greater risk with the high-voltage batteries switched off than conventional vehicles.

As with all fires, inhalation of the gases produced by the fire can harm one's health. For this reason, provide for sufficient ventilation.

**Note:** When firefighting, regardless of these general statements concerning use of lithium batteries, take into consideration the various stages in manufacturing batteries (such as cell production, lab, assembly of cells into batteries), for in these stages cell manufacturers and assembly centres can take special measures which are not suitable for the stage of finished batteries. Due to the need to take into consideration the respective circumstances for this purpose, no relevant recommendations can be made here.

## 6. Accidental releasemeasures

If the battery housing gets damaged, electrolyte can leak out. Seal batteries in an airtight plastic bag, having added dry sand, chalk powder ( $CaCO_3$ ) or vermiculite. Traces of electrolyte can be soaked up with dry paper towels. When doing so, prevent direct contact with skin by wearing safety gloves. Thoroughly rinse with water.

Use personal safety equipment appropriate for the situation (safety gloves, protective clothing, safety mask, breathing protection). For specific information about personal safety equipment, refer to the manufacturer and product-specific information.

Always proceed in accordance with the manufacturer's instructions. If required, obtain information from the manufacturer.

## 7. Handling and storage

In each case, carefully observe the warnings on batteries and the operating instructions for devices and other applications. Use only the recommended battery types. Usually only cells of the same type and design can be used. Thus, for example, lithium cells and NiMH cells or cells with a different capacity and voltage are never permitted to be used together.

Effectively prevent a short circuit of the battery poles by using suitable insulation. (e.g.: taping the terminals with insulation tape)

Lithium batteries are preferably to be stored at room temperature and in a dry location (for details, refer to the manufacturer's specifications concerning thestorage temperature range); large temperature fluctuations are to be avoided. (For example, do not store in the vicinity of heating elements, do not expose to sunshine for long periods).

If substances leak out due to damage or improper handling, be sure to comply with the manufacturer's instructions. This particularly includes the use of personal safety equipment.

When storing great quantities of lithium batteries, make an arrangement with the local authorities. In general and independent of batteries: Abuilding permit is required for storage buildings.

## 8. Exposure controls/personal protection

Lithium batteries are products, from which no substance is released under normal and reasonably foreseeable conditions of use.

#### 9. Physical and chemical properties

At this place, reference is made to the properties of the respectively used substances, which are described in the manufacturer and product-specific data sheets for lithium batteries.



#### 10. Stability and reactivity

If an upper temperature limit is exceeded (see productspecific data sheets of the manufacturer), the batteries are in danger of bursting.

When charging a rechargeable system, always be sure to comply with the upper voltage limit. If the limits are exceeded, the battery may burst or even explode. Charging a non-rechargeable system, which is not permitted, may cause the battery to burst or explode.

Likewise, the end-point voltage must not be undershot. Here as well, there is a danger of bursting.

## **11. Toxicological information**

At this place, reference is made to the toxicological information of the respectively used substances, which are described in the manufacturer and product-specific data sheets for lithium batteries.

## 12. Ecological information

At this place, reference is made to the environment-related information of the respectively used substances, which are described in the manufacturer and product-specific data sheets for lithium batteries.

#### 13. Disposal considerations

Lithium batteries are marked with the symbol of the crossedout wheeled bin(see figure).



The symbol reminds the end user that batteries are not permitted to be disposed of with household waste, but must be collected separately. Spent batteries have to be returned free of chargeto collection schemes or distributors. To prevent short circuits and associated heating up, lithium batteries are never permitted to be stored or transported in bulk form and unprotected. Suitable measures against short circuits include:

- » Placing the batteries in original packaging or a plastic bag
- >> Masking the poles
- >> Embedding in dry sand

For portable lithium batteries, collectionand recycling targets are defined as part of the European battery legislation.

Based on the European Batteries directive and as specified in Germany by the German Battery Act, all battery manufacturers and importers have to register with the German Federal Environment Agency before placing batteries on the market. The organisation of the take-back ofspent batteries must be specified at the time of registration. Acceptance of the producerobligations has to be clearly defined for all batteries before initially placing them on the market.

However, Member States maydispose f collected portable batteries or accumulators in landfills or underground storage when no viableend market is available.

Disposal of waste industrial and automotive batteries by incinerationor in landfillsis prohibited.However,residues of any batteries and accumulators that have undergone bothtreatment and recycling may bedisposed of in landfills or by incineration.





## Page 5 from 6

#### 14. Transport information

#### Important note!

Commercial transport of lithium batteries is subject to dangerous goods regulations. Transport preparations and transport are exclusively to be carried out by appropriately trained persons and/or the process has to be accompanied by corresponding experts or qualified companies.

#### **Transport regulations:**

Lithium batteries are subject to the following dangerous goods regulations and exceptions to them-in the version applicable in each case:

#### Class 9

UN 3090:	LITHIUM METAL BATTERIES
UN 3091:	LITHIUM METAL BATTERIES CONTAINED IN EQUIPMENT, or LITHIUM METAL BATTERIES PACKED WITH EQUIPMENT
UN 3480:	LITHIUM ION BATTERIES (including lithium-ion- polymer batteries)
UN 3481:	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT, orLITHIUM ION BATTERIES PACKED WITH EQUIPMENT (including lithium- ion-polymer batteries)
Tunnel category E	

Special provisions and packing instructions: ADR, RID:188, 230, 310, 348, 360, 376, 377, 636, P903, P908, P909, LP 903, LP904

IATA: A88, A99, A154, A164, A181, A182, A183, A185, A201, P965, P966, P967, P968, P969, P970

Note: For the IATA Guidance Document on lithium batteries, see <a href="http://www.iata.org/whatwedo/cargo/dgr/Pages/lithium-bat-teries.aspx">www.iata.org/whatwedo/cargo/dgr/Pages/lithium-bat-teries.aspx</a>

IMDG Code: 188, 230, 310, 360, 376, 377, P903, P908, P909, LP903, LP904 EmS: F-A, S-I Stowage category A

#### Test and inspection specifications

In accordance with the dangerous goods regulations for lithium batteries, each new type of cell or battery must have passed all tests listed in the UN Manual of Tests and Criteria, Part III, Section 38.3. This particularly applies also if multiple cells or batteries have been assembledinto new batteries (battery packs or battery assemblies).

The Manual of Tests and Criteria for lithium batteries can be downloaded from

http://www.unece.org/trans/danger/publi/manual/Rev5/ ManRev5-files\_e.html and http://www.unece.org/trans/danger/publi/manual/rev5/ manrev5-amendments.html

Used batteries are also subject to these regulations. In the case of used batteries which are intact and undamaged, usually the regulations for new batteries can be applied.

Defective or damaged batteries are subject to more stringent regulations, ranging all the way to complete prohibition of transport. The prohibition of transport applies to air transport carriers (ICAO T.I., IATA DGR -special provision A154).

However, for the transport of used – but not damaged – batteries, refer also to the corresponding special regulations (636, 377), and/or packaging instructions (P909for road transport(ADR), rail (RID) and sea (IMDG-Code).

Waste batteries and batteries which are sent for recycling or disposal are prohibited from air transport (IATA Special provision A 183).

Exceptions are to be approved by the competent authority of the country of originand the respective countryof the airline.



## 15. Regulatory information

Batteries, regardless of shape, volume, weight and use, are subject to the scope of the respective national transposition of the European Batteries Directive (2006/66/EC). This includes provisions on placing on the market, collection, treatment and recycling of batteries.

Furthermore, all batteriesneed to be marked with the "symbol of the separate collection" (crossed-out wheeled bin -cf. Section 13, Disposal)and, if the respective limit is exceeded, with the chemical symbolunderneathfor lead (Pb), cadmium (Cd) and/ or mercury (Hg) (see article21 Batteries Directive). Independent of this, a general designation of the battery system, with e.g. "Li-ion", is not excluded.

The battery manufacturer or, respectively, the importer is responsible for application of the required marking.

## 16. Other information

The instructions provide help for complying with legal specifications, but do not replace them.

The foregoing information was compiled to the best of our knowledge and belief.

It does not represent any guarantee of properties. Distributors and users of the product have their own responsibility for observing applicable laws and regulations.

Source / Editor: ZVEI – Zentralverband Elektrotechnik- und Elektronikindustrie e. V. Fachverband Batterien Lyoner Straße 9 60528 Frankfurt

Phone: +49 69 6302-283 Mail: batterien@zvei.org www.zvei.org

© ZVEI 2016 In spite of all due care, however, we cannot accept any liability for the information being complete, correct or up to date.

