



intAct Traktion-Power PzS

Low-maintenance lead-acid battery with armoured plates | wet charged

Art.No.

06TP175

Volt	6V
Capacity	185 Ah (c5), 227 Ah (c20)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	262 x 181 x 281 mm
Weight	29 kg
Pos. of Terminal	1
Terminal	1
Base plate	-









Usage



For the heaviest loads


These armored plate batteries have been specially developed for the most demanding applications. Whether as a traction battery in multi-shift operation, in work platforms for outdoor use or as a storage battery in smaller solar or wind power systems - these batteries can withstand the most adverse conditions. Our recommendation for the heaviest applications with the highest demands on the battery.

- **» For heavy professional cyclic use:** 1,000 cycles according to IEC 254-1.
- » More cycle-resistant than comparable standard lead-acid batteries gwith grid plate technology.
- » Armored plate technology: Robust and technically mature for the heaviest loads.
- » Particularly resistant to shocks in uneven outdoor use. Tubes protect active material like armor.
- **» Long service life.** Even in 2 to 3-shift operation. Durable, safe and reliable.


Size



Pos. of Terminal 1



Terminal 1



Base plate -

As of 05.09.2025

